

Product Information

Double-sided mounting tape based on an UV-cross-linked polyethylene foam coated with a modified acrylic adhesive with high adhesion on both sides. POLI-MOUNT 370 offers a high resistance against ageing, UV and weathering.

The durable elastic foam carrier guarantees a high initial tack on structured and rough surfaces like concrete and structural varnish. Composite materials with extremely different expansion rates can be mounted without tension.

POLI-MOUNT 370 is suitable for the mounting of spotlights, cover plates, plates, cable trunkings, displays, hooks and wall mounts based on different materials like PVC, ABS, polystyrene, wood, glass and ceramic.

Technical Data

| | |
|-------------------------------------|--|
| Carrier: | PE-foam |
| Adhesive: | Acrylic, modified |
| Liner: | Silicone-paper, white (90g/m ²) |
| Adhesion [N/cm]: | 3,60 +/- 10 % |
| Thickness [mm]: | 1,00 +/- 5 % |
| Temperature resistance [°C]: | -20 / +70 |

Standard Dimensions

1.500 mm x 50 m

Safety Datasheet

MSDS have not been prepared for these products, they are not subject to the MSDS requirements of the Occupational Safety and Health Administrations Hazard Communication Standard, 29 C.F.R.1910.1200 (b)(6)(v).

When used under reasonable conditions and in accordance with the Poli-Tape directions for use, these products do not present a health and safety hazard. However, use or processing of the products in a manner which is not in accordance with the directions for use may affect their performance and present potential health and safety hazards.