

POLI-MOUNT 390

Product Information

Double-sided mounting tape based on a polyethylene foam for long lasting mounting of decorative and functional trims, decals, logos, displays and components for the automotive industry.

The acrylic adhesive offers an excellent bonding with high resistance against temperature, ageing, UV and solvent and is therefore suitable for outdoor use.

The permanent elastic compressible foam carrier allows different expansion rates between the substrates. Also suitable for slightly rough and structured surfaces.

POLI-MOUNT 390 meets the required specifications of the automotive industry.

Technical Data

Carrier: PE-foam
Adhesive: Acrylic

Liner: PE-film, green

Adhesion [N/cm]: 6,50 + /-10%Thickness [mm]: 0.90 + /-5%

Temperature resistance [°C]: -40/+95

Standard Dimensions

1.250 mm x 66 m

Safety Datasheet

MSDS have not been prepared for these products, they are not subject to the MSDS requirements of the Occupational Safety and Health Administrations Hazard Communication Standard, 29 C.F.R.1910.1200 (b)(6)(v).

When used under reasonable conditions and in accordance with the Poli-Tape directions for use, these products do not present a health and safety hazard. However, use or processing of the products in a manner which is not in accordance with the directions for use may affect their performance and present potential health and safety hazards.

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17

53424 Remagen – GERMANY

Telefon: +49 (0) 2642 - 9836 0
Fax: +49 (0) 2642 - 9836 37
E-Mail: info@poli-tape.de
Internet: www.poli-tape.de

16/06/2010

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.