



PT 160

## Product Information

Transparent Application Tape based on a single sided embossed Polypropylene film, with excellent flatness. It is dimensionally stable, easy to unroll, position and will not stretch or curl.

Suitable for transferring self adhesive signs, logos and lettering produced from cast or calendered CAD/CAM plotter films with matt or brilliant surface.

Especially to be emphasised are the following properties:

- As the tape does not curl, wrinkling is avoided during lamination of large lettering. The film adjusts perfectly to the surface.
- The plasticiser resistant adhesive guarantees a strong initial tack to all types of vinyl films. The Application Tape is easily removed without leaving any residue, even after being left for a period of time.
- Suitable for wet application.
- The film can be torn transversally, which facilitates handling.
- The embossed surface allows the film to be easily unrolled without any accumulation of electrostatic charging.

## Technical Data

<b>Carrier:</b>	Polypropylene film, Orange peel surface	
<b>Adhesive:</b>	Acrylic	
<b>Adhesion [N/cm]:</b>	1,10	+/- 10 %
<b>Thickness [mm]:</b>	0,11	+/- 5 %

## Standard Dimensions

1.220 mm x 100 m

1.000 mm x 100 m

19/05/208

### POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17

53424 Remagen – GERMANY

Telefon: +49 (0) 2642 – 9836 0

Fax: +49 (0) 2642 – 9836 37

E-Mail: [info@poli-tape.de](mailto:info@poli-tape.de)

Internet: [www.poli-tape.de](http://www.poli-tape.de)

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.