



PT 190

Product Information

Application Tape based on a one-sided embossed, transparent, dimensionally stable polyethylene film. Ideally suitable for transferring of all cast and calandered PVC CAD/CAM films.

Especially to be emphasised are the following properties:

- The film has a high tensile strength which ensures an exact positioning of all letters. The excellent flatness assists the easy application.
- The acrylic adhesive is specially developed and has a constant high adhesive strength level. It can be removed without residues, even after a long period of application.
- Can be used for dry and wet application.
- Due to the embossed surface, the film unwinds easily. Static charging of the rolls is prevented.

Technical Data

Carrier:	HDPE film, pyramid surface	
Adhesive:	Acrylic, modified	
Adhesion [N/cm]:	1,40	+/- 10 %
Thickness [mm]:	0,13	+/- 5 %

Standard Dimensions

1.220 mm x 100 m

1.000 mm x 100 m

19/05/2008

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17

53424 Remagen – GERMANY

Telefon: +49 (0) 2642 – 9836 0

Fax: +49 (0) 2642 – 9836 37

E-Mail: info@poli-tape.de

Internet: www.poli-tape.de

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.