



PT 95

## Product Information

Transparent Application Tape made of an embossed cast Polypropylene film. PT 95 can be torn by hand in both directions. The product offers dimensional stability and excellent lay-flat properties.

Due to the high tack acrylic adhesive, computer cut letters, images and logos, made of cast or calendered CAD/CAM plotter films can easily be transferred.

Especially to be emphasised are the following properties:

- The excellent lay-flat property guarantees excellent lamination without wrinkles, even on large motifs.
- To guarantee an easy processing, the film can be torn by hand in both directions.
- Easy unwinding of the film with low static charge.
- The acrylic adhesive is specially developed and has a constant high adhesive strength level. It can be removed without residues, even after a long period of application.
- Suitable for dry and wet applications.

## Technical Data

<b>Carrier:</b>	Polypropylene film, pyramid surface	
<b>Adhesive:</b>	Acrylic, modified	
<b>Adhesion [N/cm]:</b>	1,50	+/- 10 %
<b>Thickness [mm]:</b>	0,14	+/- 5 %

## Standard Dimensions

1.220 mm x 100 m

1.000 mm x 100 m

19/05/2008

### POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17

53424 Remagen – GERMANY

Telefon: +49 (0) 2642 – 9836 0

Fax: +49 (0) 2642 – 9836 37

E-Mail: [info@poli-tape.de](mailto:info@poli-tape.de)

Internet: [www.poli-tape.de](http://www.poli-tape.de)

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.